



LOW COST, LOW MAINTENANCE, EASY TO USE, 16-CAMERA DVR

The Eco16 is a low cost, compact digital video recorder designed to replace the traditional VCR/multiplexer combination bringing all the benefits of digital security monitoring to the cost conscious user.

The Eco16 is designed to have the "look and feel" of a traditional CCTV system, however the user need never worry about rewinding, changing or replacing tapes as they wear out. When the available hard disk space is full, Eco16 automatically begins recording over the oldest video. Any periods of recorded video can be manually protected to prevent them from being overwritten.

The elimination of tape management issues and VCR maintenance costs means that Eco16 literally provides a fit and forget solution, with quick and easy access to recorded images if and when video needs to be reviewed.

Medium size organisations can benefit from Eco16's ability to copy incidents to CD-R. All hard disk recordings and images copied to CD provide tamper proof mechanisms approved for evidence. Playback of images from the CD is via a standard CD-ROM drive. The CD playback software will simply "auto-run" and does not require the installation of software on the users PC.

Among the many features also included as standard on Eco16 are multiway display, picture in picture viewing, password protected access, a secondary spot monitor, out of hours remote monitoring using free network viewing software, and Dedicated Micros trade mark plug and play set-up with user-friendly interface to keep installation and operator training to a minimum.

For further information, please visit the website: www.dedicatedmicros.com or contact customer services in your region.

FEATURES

- ▶ **NetVu Connected**
- ▶ **Low cost entry level digital solution for small business applications**
- ▶ **Quick and easy to install**
- ▶ **Integrated CD-R (CD writer)**
- ▶ **No VCR Tapes or maintenance**
- ▶ **Second live deterrent spot monitor output**
- ▶ **Simultaneous record, playback, background image archiving, remote viewing and playback with no loss of performance**
- ▶ **Recording of up to 50pps (PAL) 30pps (NTSC)**
- ▶ **Full remote control and observation over local Ethernet, Broadband Internet or dial up Modem connection**
- ▶ **Multiscreen, quad display and picture in picture viewing**
- ▶ **Built in Activity Detection**
- ▶ **Controlled via NetVu ObserVer over the network**



SPECIFICATION

LANGUAGES

English, French, German, Spanish, Italian, Chinese, Russian, Czech, Polish, Dutch, Hungarian, Swedish and Croatian.

CAMERAS

16 camera inputs available.
Cameras auto detected on power up.
Relay trigger option on camera fail.

HIDDEN CAMERAS

Option to view all or selected cameras, without affecting cameras recording.

MONITOR VIEWING

Main monitor:

Full screen, programmable sequence.
Programmable picture-in-picture, quad.
x2 electronic zoom on live images, freeze frame.
Mon A: Composite video BNC connector.

Spot monitor:

Full screen, programmable sequence.
Mon B: Composite video BNC connector.

SCHEDULING

Choice of day, night or weekend offers the ability to automatically:

- Switch activity on/off
- Alter the record rate for standard, alarm and activity recording
- Activation is via timer

ACTIVITY DETECTION

Programmable 16 x 16 masking grid for each camera view.
5 levels of sensitivity.

Options:

- Trigger light duty relay output 500mA @ 20V max

ALARMS

1 normally open global alarm contact available via back panel.
16 normally open/closed camera specific alarm contacts via back panel.
• Main monitor display of last alarm, 2 second dwell per alarmed camera, return to pre-alarm display
• Trigger light duty relay output 500mA @ 20V max

SEARCH AND PLAYBACK

- One touch playback
- Frame advance/rewind, fast picture search and pause keys
- Event list, including event list filter with unique quadrant preview facility
- GOTO time and date
- Playback in quad, picture in picture and full screen

RECORDING

Playback and record to hard disk simultaneously.

Hard disk sizes are rapidly increasing in capacity. Please contact customer services or DM web site, for latest available disk capacity for Eco16.

Protected images:

The end user can manually configure sections of recorded images to be permanently protected from overwrite. The system can also be configured to protect images automatically when the global alarm is activated.

RECORD RATE

Maximum record rate up to 50pps (PAL) and 30pps (NTSC)

TIMED EXPIRY

- Timed expiry option allows images to be held for a selected number of days
- Images on the disk, which are older than the number of days, selected are not accessed

EVENT COPYING

Event sequences and user defined recorded sequences can be saved to the internal CD-R drive of Eco16.

The sequences of images are digitally signed for authentication purposes. Playback of images from the CD is via a standard CD ROM drive. The CD playback software will auto-run and does not require the installation of software on the users PC.

DIGITAL SIGNATURE

The use of digital signatures makes it possible to detect whether single image or a sequence of images have been tampered with.

ECO16 NETWORKING CAPABILITIES

Standard Ethernet connection provides live and recorded viewing on a networked PC using DM's NetVu ObserVer or web pages using Internet Explorer. Network viewing is independent and does not affect the recording or local operation. The amount of bandwidth the Eco16 uses on the network can be adjusted by the bandwidth limitation option.

Network ObserVer software features include:

- Live full, quad or multiway format screens
- Fast forward and rewind, playback and frame advance/rew
- GOTO time and date and unique quadrant event review
- File export over the network
- Copy single images as JPEG and sequences of images to save to PC
- Configurable password protection
- Replay server feature removes the need for additional viewing software when video is downloaded to a PC

Web pages features include:

- Viewing of live images in single, quad or multiway format
- Playback in single, quad or multiway format including GOTO function
- Password authentication
- System configuration via web pages

COLOUR RESOLUTION

Sampling rate: 13.5 MHz to CCIR 601
Number of pixels: PAL 704h x 512v
NTSC 704h x 448v
16.8 million colours 256 levels of grey, 8-bit luma.

COMPRESSION

JPEG format files. 2CIF, CIF and QCIF compression.
User definable file compression size.

ECO16 DATA

RS-232 serial port.
485-Bus support for IR interface.
1x Ethernet RJ-45 10/100Base-T connection.

CD-RW

Built-in slim-line CD Writer for Compact Disk Recordable Media.

TEMPERATURE RANGE

Operating temperature 5 – 40°C (41-104 °F).

RELATIVE HUMIDITY

5% - 85% Non-condensing.

DIMENSIONS

DVR
66mm (H) x 440mm (W) x 409mm (D).
2 5/8"(H) x 17 5/16" (W) x 16 1/8" (D).

WEIGHT

DVR
5.9Kg (13lbs) without PSU.
6.6Kg (14.5lbs) with PSU.

POWER SUPPLY

Input Voltage:
100 – 230 VAC 50/60 Hz.
Output Voltage: 5, +12, -12 VDC.

BUILT-IN CD WRITER RANGE

DESCRIPTION	SHORT CODE
16 CAMERA COLOUR DUPLEX WITH CDR 25PPS 160GB	ECO16 CD - 160GB
16 CAMERA COLOUR DUPLEX WITH CDR 25PPS 300GB	ECO16 CD - 300GB

Please contact customer services for latest available disk capacity.

PLEASE CHECK THE WEBSITE FOR DETAILS OF COMPATIBLE PRODUCTS AND OTHER LATEST DEVELOPMENTS

FOR FURTHER INFORMATION PLEASE CONTACT

Dedicated Micros UK
Dedicated Micros USA

1200 Daresbury Park, Daresbury, Warrington, WA4 4HS - Tel: +44 (0) 845 600 9500 Fax: +44 (0) 845 600 9504
14434 Albemarle Point Place, Suite 100, Chantilly, Virginia 20151 - USA Freephone: 800 864 7539
Tel: +1 703 904-7738 Fax: +1 703 904-7743 and 23456 Hawthorne Blvd. Suite 100, Torrance, CA 90505
Tel +1 310 791-8666 Fax: +1 310 791-9877

Dedicated Micros Germany

Neckarstraße 15a, 41836 Hüchelhoven, Germany - Tel: +49 243 352 580 Fax: +49 24 33 52 58 10

Dedicated Micros France

9-13 rue du Moulinet, 75013 Paris, France - Tel: +33 1 45 81 99 99 Fax: +33 1 45 81 99 89

Dedicated Micros Asia

16 New Industrial Road, #03-03 Hudson TechnoCentre, Singapore 536204 - Tel : +65 62858982 Fax : +65 62858646

Dedicated Micros Australia

2/9 Packard Avenue, Castle Hill, NSW 2154, Australia - Tel: +612 9634 4211 Fax: +612 9634 4811

Dedicated Micros New Zealand

PO Box 180046, Luckens Point, West Harbour, Auckland 0663, New Zealand - Freephone: 0800 364 276
Tel: +64 (09) 448 2366 Fax: +64 (09) 448 2369

Dedicated Micros Malta

BLB017, Bulebel Industrial Estate, Zejtun, ZTN08, Malta - Tel: +356 21483 673/4 Fax: +356 21449 170

Dedicated Micros Middle East


Building 12, Suite 302, P.O.Box 500291, Dubai Internet City, Dubai, UAE - Tel: +971 (4) 390 1015
Fax: +971 (4) 390 8655

Dedicated Micros Slovenia

Delavska cesta 24, 4208 Sencur, Slovenia - Tel: +386 4 279 18 90 Fax: +386 4 279 18 91

Dedicated Micros Benelux

Joseph Chantraineplantsoen 1, 3070 Kortenberg, Belgium - Tel: +32 2751 3480 Fax: +32 2751 3481



www.dedicatedmicros.com

The manufacturer reserves the right to change the specification without notice.



All trademarks are courtesy of registered owners.
The DM logo is a trademark of Dedicated Microcomputers group Ltd.
NetVu Connected is a trademark of the AD group.
MKT-EC16-D-006E